MESH | M1



M1 Dune



Maize



Sage



Autumn



Currant



Crimson



Cove



Pacific



Midnight



Haze



Smoke



Carob



Carbon



Onyx

allseating

Technical Information

Width/ Pattern	Applicable Chairs	Fiber Content & Backing	Weight	Protective Finish	Abrasion Resistance	Light-fastness	Approx. Repeats	CI. Code
M1 56"	Entail, Inertia, Levo, M.O.	100% Polyester	407 g/m²	N/A	100,000 Double Rubs	Level 4	Full Repeat Shown	N/A

EXPLANATION OF ACT ICONS FOR UPHOLSTERY

Fire Retardancy

Flammability testing determined as fabric's resistance to burning.

Colorfastness to Wet and Dry Crocking

Colorfastness to wet & dry crocking refers to the rubbing off of color from the fabric onto clothing, hands or other materials and can occur under wet or dry conditions.

Colorfastness to Light

Colorfastness to light is the degree to which fabric will retain its color when exposed to light.

Physical Properties

3 physical property tests include: brush pill test to determine a fabric's pilling. Breaking/tensile strength is the ability of a fabric to withstand tension without breaking or tearing. Seam slippage is the pulling apart of fabrics at the seams.

Abrasion

Abrasion is the ability of a fabric to withstand damage from wear and rubbing. There is a general contract specification as well as heavy duty specification.

TORONTO
5800 Avebury Road, Unit 2
Mississauga, ON L5R 3M3

CHICAGO*
325 North Wells Street, Suite 210
Chicago, IL 60654

NEW YORK*
1140 Broadway, Suite 307
New York, NY 10001

TO VIEW OUR ENTIRE MESH COLLECTION, VISIT ALLSEATING.COM
T 1 800 563 3502 F 1 800 272 9911

SKU BF9945

Printed in Canada 01/2019

*By appointment only